



TIGO'S IMPACT

STANDARD: EN 420:2003+A1:2009 & EN 388:2016

IDEAL APPLICATIONS	INDUSTRY
Engagement and release of drill string slips	Petrochemical
Drilling assembly and completion	Automotive
Handling jagged metal	Glass
Assembly, machining / stamping / cutting production services / processing drilling / extraction	Metal structure construction
Heavy equipment handling & servicing	Machinery & Equipment's

LINER TYPE	COATING
UHMWPE /Glass fiber / steel / Polyester/ lycra	Palm sandy nitrile coating with thumb crotch

CUFF	CERTIFICATION
Velcro adjustable	EN388: 2016 – 4544DP

FEATURES
UHMWPE (Ultra high molecular weight polyethylene) cut level 5 / D liner
palm sandy nitrile coated
Thermo plast rubber padding on the back to reduce sudden impact force upto 9N
Seamless knitted liner for ultimate comfort and higher flexibility



LINER COLOUR	COATING COLOUR
Grey	Black palm / Yellow-black padding

ADVANTAGE
Thermo plast rubber padding on the back & velco adjustable strap on the wrist. Thumb crotch for added protection

APPLICATION
Assembly line, assembling metal parts and components
Handling sharp or irregular metal pieces
Molding, plastic injections, hardware assembly

STORAGE
Store in cool and dry place
Do not store in direct / high heat or sunlight
Can be stored and transported in their original cartons

LAUNDERABLE	PACKING
No	120 pairs per carton