



TIGO'S RAPID

STANDARD: IS: 15298-Part 2

INDUSTRY	
Construction & infrastructure	Warehouse & transport
Service industry	Manufacturing - All types of small manufacturing industries

Standard Features



Additional



COMPONENT	MATERIAL	ADVANTAGE
Upper	Synthetic Leather: Black	Excellent tensile & tear strength, durability, Water resistance etc.
Lining	Non-woven Black Air-Mesh Lining	Keeps the foot warm & dry and balance the moisture inside the shoe
Toe Cap	Steel Toe Cap 100J	Protective reinforcement in the toe which protects the foot from falling objects
Sole	Single Density PVC Black	Oil & Fuel Resistant, Anti-static, Slip Resistant (SRC), Anti-skid Design
Insocks	Laminated EVA, 3 mm	Improve shock absorption, provides pain relief, ankle & leg injuries with extra comfort

COLLAR	TONGUE	EYELET	LACE	THREAD
Foam padded	PU Alfa with 10 mm Foam	Coated round	Nylon Grey & Black, 100 cm	6 Ply

FEATURES	STORAGE		
Very good physical & chemical properties	Keep away from sources of heat		
High tear & tensile endurance	Keep in a dry, well-ventilated space		
Excellent resistance to abrasion	Keep in cleaned and ready to be used condition		
Excellent breathability	APPLICATION		
Slip resistance sole-SRC	Construction & infrastructure		
Durability	Warehouse & transport		
Ease of care	Manufacturing - All types of small manufacturing industries		
PVC Sole			
Water resistance upper			
Anti-bacterial & Odor free			
Steel toe cap - 100 J			
PACKING	SIZE	CLEANING	
24 pairs per carton	6 to 12	Wipe with a soft cotton cloth, soaked in warm water and mild liquid soap. Dry it in shaded & ventilated place.	

Tigo's