



TIGO'S TITAN

STANDARD: IS: 15298-Part 2

INDUSTRY

Automotive	Oil & Gas
IT & Technology - Telecom	Production Process, Chemical industries

Standard Features



Additional



COMPONENT	MATERIAL	ADVANTAGE
Upper	Water-Repellent Microfiber Upper: Durable Microfiber that protects against moisture while offering comfort throughout the workday.	Excellent tensile & tear strength, durability, Water resistance etc.
Lining	Breathable Polyamide Lining: Keeps your feet cool and dry by quickly absorbing moisture	Keeps the foot warm & dry and balance the moisture inside the shoe
Toe Cap	Steel Toe Cap, 200 Joules (Composite As per request)	Protective reinforcement in the toe which protects the foot from falling objects
Sole	Double Density PU Black / Grey	Oil & Fuel Resistant, Heat Resistant up to 120 Degree Celsius for 1 minute
Insocks	Laminated EVA, 6 mm	Improve shock absorption, provides pain relief, ankle & leg injuries with extra comfort

COLLAR	TONGUE	EYELET	LACE	THREAD
Foam padded	PU Alfa with 10 mm Foam	5 pairs Brass Anti-rust Black round	Nylon Black, 100 cm	6 Ply

FEATURES

Very good physical & Mechanical properties
High tear & tensile endurance
Excellent resistance to abrasion
Excellent breathability
Slip resistance sole-SRC
Durability
Ease of care
Steel toe cap – 200J (Composite as request)
Water resistance upper
Anti-bacterial & Odor free
Microfiber Upper good finished

STORAGE

Keep away from sources of heat
Keep in a dry, well-ventilated space
Keep in cleaned and ready to be used condition

APPLICATION

Production Process
Transport: Automotive
Oil & Gas, Chemical industries

PACKING	SIZE	CLEANING
12pairs per carton	5 to 12	Wipe with a soft cotton cloth, soaked in warm water and mild liquid soap. Dry it in shaded & ventilated place.

Tigo's