



TIGO'S TD-7000Y

STANDARD: IS: 15298-Part 2

INDUSTRY

Automotive	Clean room surface
Airport	Epoxy industries

Standard Features



Additional



COMPONENT	MATERIAL	ADVANTAGE
Upper	Premium engineered imported knitted textile fabric combined with durable KPU overlays for a modern, sporty look and rain forced protection.	Excellent tensile & tear strength, durability, Water resistance etc.
Lining	Non-woven Black Air-Mesh Lining, 270 gsm	Keeps the foot warm & dry and balance the moisture inside the shoe
Toe Cap	Composite Toe Cap, 200 Joules	Protective reinforcement in the toe which protects the foot from falling objects
Sole	Single Density PU Black	Oil & Fuel Resistant, Heat Resistant up to 120 Degree Celsius for 1 minute
Insocks	Laminated EVA, 6 mm	Improve shock absorption, provides pain relief, ankle & leg injuries with extra comfort

COLLAR	TONGUE	EYELET	LACE	THREAD
Foam padded	PU Alfa with 10 mm Foam	5 pairs rubber molded	Nylon Black, 100 cm	6 Ply

FEATURES

Very good physical & Electrical properties
High tear & tensile endurance
Excellent resistance to abrasion
Excellent breathability
Slip resistance sole-SRC
Durability
Ease of care
Composite toe cap – 200J
Water resistance upper
Anti-bacterial & Odor free
Sporty Look

STORAGE

Keep away from sources of heat
Keep in a dry, well-ventilated space
Keep in cleaned and ready to be used condition

APPLICATION

Airport
Automotive Industrial Safety
Epoxy Flooring

PACKING	SIZE	CLEANING
12pairs per carton	5 to 12	Wipe with a soft cotton cloth, soaked in warm water and mild liquid soap. Dry it in shaded & ventilated place.

Tigo's