



TIGO'S TD-701 DD

STANDARD: IS: 15298-Part 2

INDUSTRY

Construction & infrastructure	Warehouse & transport
Automotive	Manufacturing - All types of manufacturing industries

Standard Features



Additional



COMPONENT	MATERIAL	ADVANTAGE
Upper	Genuine Leather: Buffalo Barton Print Black Waterproof DIN-S3	Excellent tensile & tear strength, durability, Water resistance etc.
Lining	Non-woven Black Air-Mesh Lining	Keeps the foot warm & dry and balance the moisture inside the shoe
Toe Cap	Steel Toe Cap, 200 Joules	Protective reinforcement in the toe which protects the foot from falling objects
Sole	Double Density PU Grey / Black	Oil & Fuel Resistant, Anti-static, Heat Resistant up to 120 Degree Celsius for 1 minute
Insocks	Laminated EVA, 4 mm	Improve shock absorption, provides pain relief, ankle & leg injuries with extra comfort

COLLAR	TONGUE	EYELET	LACE	THREAD
Foam padded	PU Alfa with 10 mm Foam	4 pairs Anti-Rust Brass Black Round	Nylon Grey & Black, 100 cm	6 Ply

FEATURES	STORAGE
Very good physical & chemical properties	Keep away from sources of heat
High tear & tensile endurance	Keep in a dry, well-ventilated space
Excellent resistance to abrasion	Keep in cleaned and ready to be used condition
Excellent breathability	APPLICATION
Slip resistance sole-SRC	Construction & infrastructure
Durability	Automotive Industrial Safety
Ease of care	Manufacturing - All types of manufacturing industries
Antistatic PU Sole	PACKING
Water resistance upper	SIZE
Anti-bacterial & Odor free	CLEANING
Steel toe cap - 200 J	18pairs per carton
	5 to 12
	Wipe with a soft cotton cloth, soaked in warm water and mild liquid soap. Dry it in shaded & ventilated place.

Tigo's