TiGO'S®
ALL SAFETY RULES

Scan Here For More Info

TIGO'S TG-102 DD

STANDARD: IS: 15298-Part 2

INDUSTRY	
Construction & infrastructure	Warehouse & transport
Automotive	Manufacturing - All types of manufacturing industries

Standard Features

Additional

COMPONENT	MATERIAL	ADVANTAGE
Upper	Genuine Leather: Buffalo Barton Print Black Waterproof DIN-S3 Black with Reflector for Night Visibility	Excellent tensile & tear strength, durability, Water resistance etc.
Lining	Non-woven Black Air-Mesh Lining, 270 gsm	Keeps the foot warm & dry and balance the moisture inside the shoe
Toe Cap	Steel Toe Cap, 200 Joules	Protective reinforcement in the toe which protects the foot from falling objects
Sole	Double Density PU Grey / Black	Oil & Fuel Resistant, Anti-static, Heat Resistant up to 120 Degree Celsius for 1 minute
Insocks	Laminated EVA, 6 mm	Improve shock absorption, provides pain relief, ankle & leg injuries with extra comfort

COLLAR	TONGUE	EYELET	LACE	THREAD
Foam padded	PU Alfa with 10 mm Foam	4 pairs Anti-Rust Brass Black Round	Nylon Grey & Black, 100 cm	6 Ply

FEATURES
Very good physical & chemical properties
High tear & tensile endurance
Excellent resistance to abrasion
Excellent breathability
Slip resistance sole-SRC
Durability
Ease of care
Antistatic PU Sole
Water resistance upper
Anti-bacterial & Odor free
Steel toe cap - 200 J

STORAGE
Keep away from sources of heat
Keep in a dry, well-ventilated space
Keep in cleaned and ready to be used condition

APPLICATION
Construction & infrastructure
Automotive Industrial Safety
Manufacturing - All types of manufacturing industries

PACKING	SIZE	CLEANING
10pairs per carton	5 to 12	Wipe with a soft cotton cloth, soaked in warm water and mild liquid soap. Dry it in shaded & ventilated place.

Tigo's

Aatmiya Industrial Park- 2,
Plot No. 28, Por, Vadodara 391423

E-mail: info@kevalsafety.com

Website: www.kevalsafety.com